

PRODUCT DATA SHEET



FPC-5: Particleboard Core Door 5-Ply

SPECIFICATIONS

Max Size: Singles: 4'0" x 10'0"; Pairs: 8'0" x 10'0"

Transoms: Available. Contact Fortress for size restrictions. 1-

Thickness: 3/4", 1-3/8" & 2-1/4" Particleboard which

Core: complies with ANSI A208.
11-LD2 or 1-LD1.

Veneers: Any commercially available wood veneered door face. WDMA "A" Grade, Book & Running match is standard), MDO, Primed Hardboard and Decorative Plastic Laminate.

Stiles: 1-1/4" min. (before trim) Structural Composite Lumber (SCL) with compatible veneer band, decorative laminate or compatible hardwood.

Rails: 2-1/4" min. (before trim) mill option wood or SCL.

Factory Finish: UV Cured Acrylic Epoxy. Clear or stained. Fortress Door standard colors or custom color match available.

Adhesives: Door assembly – Type I
Veneers – Type II

Lites*: Metal vision frames open for 1/4" wire glass or 3/16" Firelite NT glass.
Max visible glass 1296 sq in;
max width 36", max length 54"
Louvers not available in FPC 20 minute.
Wood lip or wood flush available

Blocking: : Top rail, bottom rail, stiles and special blocking can be specified to meet specialized hardware requirements.

Warranty: Fortress doors are warranted for interior use only. One year (standard), 2 year and 5 year are repair, replace or refund only. Life of Installation Warranty with additional benefits available.

Machining: Prefitting, beveling, lock and hinge mortise and other hardware preps available.

Fire Rating: 20-minute available

Neutral (standard) and Positive Pressure Category B** Intertek Testing Service/Warnock Hersey international (ITS-WHI) 1-3/4" or 1-3/8" (single only)

Standards: ANSI/WDMA I.S.1A and AWI Section 1300

*Minimum 5.5" from any edge of door including hardware cutouts, to meet labeling and warranty requirements.

**Contact Fortress Door for size restrictions

