

PRODUCT DATA SHEET



FPC-9: Primed Hardboard

SPECIFICATIONS

Max Size: Singles: 4'0" x 10'0", Pairs available.
Transoms: Available.
Thickness: 1-3/4", 1-3/8" & 2-1/4"
Core: Particleboard which complies with ANSI A208.1 1-LD2 or 0_LD-1.

Door

Facing: Primed Hardboard
Stiles: Mill Option
Rails: 2-1/4" min, (before trim) mill option
Adhesives: Door assembly - Type 1
Lites*: Metal vision frames open for 1/4" wired glass or 3/16" Firelite NT glass. Max visible glass 1296 sq in; max width 36", max length 54" Wood lip, wood flush or Metal Vision Panel.
Blocking: Top rail, bottomrail, stiles and special blocking can be specified to meet specialized hardware requirements.
Warranty: Fortress doors are warrantied for interior use only. One year (standard), 2 year and 5 year are repair, replace or refund only. Life of installation. Warranty with additional benefits available.
Machining: Prefitting, beveling, lock and hinge mortise and other hardware preps available.
Fire Rating: 20 minutes available.
Neutral (standard) and Positive Pressure Category B**
Intertek Testing Service/Warnock Hersey (ITS-WHI) 1-3/4" or 1 3/8" (single only)

*Minimum 5.5" from any edge of door including hardware cut-outs, to meet labeling and warranty requirements.

**Contact Fortress Door Company for size restrictions.

