

FPC-9: Particleboard Core Door 9-Ply

SPECIFICATIONS

- Max Size:** Singles: 3'0" x 8'0"
- Transoms:** Available. Contact Five Lakes for size restrictions.
- Thickness:** 1-3/4", 1-3/8" & 2-1/4"
- Core:** Particleboard which complies with ANSI A208.1 1-LD2 or 1-LD1.
- Veneers:** Rotary Natural Birch and Plain Sliced Red Oak
- Stiles:** 1-1/4" min. (before trim) Structural Composite Lumber (SCL) with compatible veneer band, decorative laminate or compatible hardwood.
- Rails:** 2-1/4" min. (before trim) mill option hardwood or SCL.
- Factory Finish:** UV Cured Acrylic Epoxy. Clear or stained. Fortress Door standard colors or custom color match available.
- Adhesives:** Door assembly – Type I
Veneers – Type II
- Lites*:** Metal vision frames open for 1/4" wired glass or 3/16" Firelite NT glass. Max visible glass 1296 sq in; max width 36", max length 54" Wood lip, wood flush or Metal Vision Panel.
- Blocking:** Top rail, bottom rail, stiles and special blocking can be specified to meet specialized hardware requirements.
- Warranty:** Five Lakes doors are warranted for interior use only. One year (standard), 2 year and 5 year are repair, replace or refund only. Life of Installation Warranty with additional benefits available.
- Machining:** Prefitting, beveling, lock and hinge mortise and other hardware preps available.
- Fire Rating:** Neutral (standard) and Positive Pressure Category B** Intertek Testing Service/Warnock Hersey International (ITS-WHI) 1-3/4" 20-minute available.
- Standards:** FPC-9 doors are economical quality alternative to our 5-ply line.

*Minimum 5.5" from any edge of door including hardware cutouts, to meet labeling and warranty requirements.

**Contact Fortress Door for size restrictions

